



SEA-Drive® 180
Class 7 - 8
SEA ... the Future

SEA-Drive® 180a (Class 7 - 8) is built on a cab/chassis platform with a GVWR range from 30,000 lbs to 39,700 lbs, and a 2,581 lb-ft (3,500 Nm) electric motor. The 220 kWh battery pack option, delivers class leading range of up to 150 miles* and a typical breakeven period of less than 4 years without grants and subsidies.

SEA-Drive® 180b (Class 8) is built on a cab/chassis platform with a GVWR range from 39,000 lbs to 57,500 lbs, and a 2,851 lb-ft (3,500 Nm) electric motor. The 220 kWh battery pack option, delivers class leading range of up to 125 miles* and a typical breakeven period of less than 4 years without grants and subsidies.

SPECIFICATIONS

SEA-Drive® 180

SEA-Drive® 180	Charging
Powered by SEA-Drive® 180	Standard charging provided through Type 1, Level 2, Single Phase (208/240 VAC) up to 19.2 kW
Range: Up to 150 miles* (unladen)	Charger is SAE J1772 Compliant
Operating temperature range: 0°F to 140°F	Charge Time: Approx. 12 hours
100% Electric Power-System 180a	<i>Optional</i> Fast charging provided through standard CCS Type 1, Level 3, DC fast charging up to 120kW
Type: AC Asynchronous Motor	Batteries
Continuous power: 200 hp (150 kW)	220 kWh battery capacity
Maximum power: 335 hp (250 kW)	Life Cycle: Up to 10 Years
Maximum torque: 2,500 lb-ft (1,844 Nm)	Cell Type: Lithium-Ion (LiNiMnCoO ₂) - Known as NMC
Efficiency: 95% peak efficiency	Energy Density: 127.7 Wh/Kg
100% Electric Power-System 180b	HVAC - Air Conditioning and Heating
Type: Permanent Magnet AC Motor	Electric integrated HVAC System - 6.5 kW, HVDC powered
Continuous power: 260 hp (195 kW)	Electric PTC heater 6kW, HVDC powered
Maximum power: 470 hp (350 kW)	
Maximum torque: 3,500 lb-ft (2,581 Nm)	
Efficiency: 95% peak efficiency	
System Warranty[#]	Telematics SEA-Connect® <i>Optional</i>
5 years for batteries	Ability to provide vehicle and driver related data
System Warranty: 3 years or 50,000 miles [#]	Accessible via a secure telematics portal



Most Cost Effective Power-System in the World



Unique Mid Mounted Batteries for Safety & Dynamics



Adaptable to Most OEM Glider Platforms



Lower Maintenance & Operating Costs - No Fuel, Few Moving Parts



Zero Emissions - Reduce Your Carbon Footprint



Adaptable to New & Used Chassis - Repower Existing Vehicles



Single Phase 240V On Board Charger - the Biggest Charging Network In The World



Integration with Body Suppliers - 100% Electric Power to Operate Ancillaries



Powerful Handling with a Smooth Ride



Driver Comfort, Health & Safety - No Noise, No Fumes, No Heat

*Range figures are intended for comparison purposes only and are based on unladen, cab chassis or van test drive conditions. Actual range achieved will depend upon a number of factors including load and body design, road conditions and topography, regenerative braking configuration and utilisation of electrical accessories.

SEA Electric LLC. The information on this brochure was correct at the time of printing, all specifications are subject to change without notice. The information in this brochure is general in nature. To the extent permitted by law SEA Electric LLC is not liable by any person as result of reliance on the content of this brochure.

[#]Subject to conditions outlined in SEA Electric Warranty brochure. For more details visit the SEA Electric website.