



## SEA-Drive® 100

*SEA ... the Future*

SEA-Drive® 100 is built on a cab/chassis platform with a GVM range from 4.5t to 6.5t, and a 1,000 Nm electric motor. The 100 kWh battery pack option delivers class leading range of up to 275km\* and a typical break-even period of less than 4 years.

# SPECIFICATIONS

## SEA-Drive® 100

### SEA-Drive® 100

Powered by SEA-Drive® 100
Range: Up to 275km* (unladen)
Operating temperature range: -20°C to 50°C

### 100% Electric Power-System

Type: AC Asynchronous Motor
Continuous power: 59 kW
Maximum power: 108 kW
Maximum torque: 1,000 Nm
Efficiency: 95% peak efficiency

### Batteries

100kWh battery capacity
Life Cycle: Up to 10 Years
Cell Type: Lithium-Ion (LiNiMnCoO <sub>2</sub> ) - Known as NMC
Energy Density: 127.7 Wh/Kg

### Charging

Standard charging using three-phase 32amp on board charger with 5 pin plug, up to 22kW
DC/DC converter is 3kW with 24V power supply
Charge Time: Approx. 4 hours up to 80% charge
<i>Optional</i> Fast Charging System

### HVAC - Air Conditioning and Heating

Electric integrated HVAC System - 6.5 kW, HVDC powered
Electric PTC heater 6kW, HVDC powered

### Telematics SEA-Connect® *Optional*

Ability to provide vehicle and driver related data
Accessible via a secure telematics portal

### System Warranty

5 years for batteries <sup>#</sup>
Remaining system warranty same as OEM chassis <sup>#</sup>



Most Cost Effective Power-System in the World



Unique Mid Mounted Batteries for Safety & Dynamics



Adaptable to Most OEM Glider Platforms



Lower Maintenance & Operating Costs - No Fuel, Few Moving Parts



Zero Emissions - Reduce Your Carbon Footprint



Upgradable Plug and Play Architecture



Three-phase 32amp On Board Charger - the Biggest Charging Network In The World



Integration with Body Suppliers - 100% Electric Power to Operate Ancillaries



Powerful Handling with a Smooth Ride



Driver Comfort, Health & Safety - No Noise, No Fumes, No Heat

\*Range figures are intended for comparison purposes only and are based on unladen, cab chassis or van test drive conditions. Actual range achieved will depend upon a number of factors including load and body design, road conditions and topography, regenerative braking configuration and utilisation of electrical accessories.

SEA Electric Limited NZBN 9429046806604. The information on this brochure was correct at the time of printing, all specifications are subject to change without notice. The information in this brochure is general in nature. To the extent permitted by law SEA Electric Limited is not liable by any person as result of reliance on the content of this brochure.

<sup>#</sup>Subject to conditions outlined in SEA Electric Warranty brochure. All SEA Electric warranties are subject to mandatory prescribed terms under Consumer Guarantee Act (CGA) including customer guarantees. For more details visit the SEA Electric website which explains SEA Electric warranties in more detail.